Sodium Waterglass (Comp. A)

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Sodium Waterglass Comp. A

1.2 Relevant identified uses of the substance or mixture and uses advised against

"A" component for water glass - polyisocyanate based twocompo-nent synthetic resin. The synthetic resin (components "A"+"B") is used for the lining of sewer pipes and manholes. The application has to be carried out under professional, industrial conditions by persons having proper previous training.

1.3 Details of the supplier of the safety data sheet

Company S1E Limited Street/POB Cooper House, Unit 2 S72 7BQ, Barnsley Postcode/City/Country Phone +44 (0)1226 396 015 contact@s1e.co.uk E-mail

1.4 Emergency telephone number

Medical emergency information in case of intoxication

+44 (0) 845-408-9575 Merseyside/UK Emergency telephone number

2. Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard classes / categories	Hazard statements
Skin irrit. 2	H315
Eye dam. 1	H318

2.1.2 Classification according to 67/548/EEC

Classifi cation	R-phrases	S- phrases
Xi	R38	S26
	R41	S36/37/39

Safety Datasheet Version 3 1 / 18 01 202

2.2 Label elements

according to Regulation (EC) 1272/2008 (CLP) & 67/548/EEC

2.2.1	Labelling according to Regulation (EC) 1272/2008 (CLP)	
	Hazard pictogram	
	Signal word	Attention
	Hazard statements	
	H315	Causes skin irritation.
	H318	Causes serious eye damage.
	Precautionary statement	s
	P262	Do not get in eyes, on skin, or on clothing.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact len- ses, if present and easy to do. Continue rinsing.
2.2.2	Labelling according to 67/	548/EEC
	Xi	×
	R38	Irritating to skin.

R38	Irritating to skin.	
R41	Risk of serious damage to eyes.	
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.	
Hazard determining component(s) for labelling:		

Silicid acid, sodium salt (CAS: 1344-09-8, EINECS: 215-687-4).

2.2.3 Other hazards None known.



according to Regulation (EC) 1272/2008 (CLP) & 67/548/EEC

3. Composition/information on ingredients

Substances/mixtures: Substance				
Chemical name	EC-No.	CAS-No.	REACH-No.	Content (%)
Silicic acid sodium salt	215-687-4	1344-09-8	01 2110448725 31 0000	25 50
(Molar ratio Na20 :	215 007 4	1344 07 0	01-2117440723-31-0000	23 - 30
SiO2 = 1 : > 1.6 - < 2.6)				

4. First aid measures

4.1 Description of first aid measures

General information	No special measures necessary
If inhaled	No special measures necessary
On skin contact	In case of contact with skin, wash off immediately with plenty of water. Do not allow the product to dry on the skin. Consult a doctor if skin irritation persists.
On contact with eyes	Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
On ingestion	Immediately rinse mouth and drink plenty of water, do not induce vomiting, seek medical attention immediately.
Hints for the physician	This product contains alkali silicates.

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing meida	Product itself is non-combustible; adapt fire extinguishing measures to
	surrounding areas.
Non-suitable	Compatible with all usual
extinguishing media	extinguishing media.

5.2. Special hazards arising from the substance or mixture

None known.

5.3. Advice for firefighter

Safety

Datasheet

Version 3 1 / 18 01 202

Special protective	In case of combustion use a
equipment	suitable breathing apparatus.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Avoid contact with skin, eyes and clothing. High risk of slipping due to leakage/spillage of product.

6.2. Environmental precautions

Do not allow to enter drains or waterways.

6.3. Methods and material for containment and cleaning up

Take up with absrobent material (e.g. sand, kieselguhr, universal binder). Rinse away rest with plenty of water.

7. Handling and storage

7.1 Precautions for safe handling

Observe the usual precautions for handling chemicals. Open and handle container with care.



7.2 Conditions for safe storage, including any incompabilities

Requirements for atณ ବଡ଼େ ଶ୍ୱେ୭ms	Keep only in the original container.
Further information on storage conditions	Protect from frost.
Recommended storage temperature	Value 5 - 45°C.
VCI storage category	12 non-combustible liquids.
Storage stability	Under correct storing conditions the product is stable for at least 12 months.

8. Exposure controls/personal protection

8.1 Control parameters

No exposure limit value known.

8.2 Exposure controls

General protective Observe the usual precautions when and hygiene measures handling chemicals. Wash hands before breaks and after work. Do not eat, drink or smoke during work time.

Occupational exposure controls

Respiratory protection	Breathing apparatus in the event of aerosol or mist formation. Short term: fi Iter apparatus, Filter B.
Hand protection	Gloves (alkali-resistant) Appropriate material: Latex KCL Lapren 706 / 0.6 mm / 480 min.
Eye protection	Safety glasses with side protection shield.
Skin protection	Clothing as usual in the chemical industry.

Safety Datasheet Version 3.1 / 18.01.2022

according to Regulation (EC) 1272/2008 (CLP) & 67/548/EEC

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	liquid, clear, colourless to slightly yellow
Odour	odourless
Odour threshold	no data
pH-value	13-14
Melting point/ freezing point	no data
Boiling range	appr. 100 °C
Flash point	not fl ammable
Evaporation rate	no data
Flammability (solid, gaseous)	not ignitable
lgnitable, explosive range	no data
Vapour pressure	no data
Vapour density	no data
Density	appr. 1,55 kg/l (at 20 °C)
Solubility	completely miscible
Partition coefficient n-octanol/water	not applicable
Self-ignition temperature	no data
Decomposition temperature	no data
Viscosity	appr. 600 mPa.s (at 20 °C)
Explosive properties	no data
Oxidising properties	no data

9.2 Other information

Not applicable.



(Comp. A)

10. Stability and reactivity

Conditions to avoid	Protect from frost.
Materials to avoid	Acids
Hazardous decom- position products	No hazardous decomposition products known.

11. Toxicological information

Information is related to the product, data are used as cross reference.

Acute toxicity

Acute oral toxicity

Remarks	The toxicological data shown are those obtained from tests on products of simi- lar composition.	12.	Ecological informa	tion
Reference substance	Slilicic acid, sodium salt (Molar ratio Na ₂ O : SiO ₂ = 1 : 2.0; 40-50%) Species rat		IInformation is related t reference.	o the p
	LD50 > 2000 mg/kg		Fish toxicity	
	Source data of supplier		Remarks	Ecc
Reference substance	Slilicic acid, sodium salt (Molar ratio			sim
	Na ₂ O : SiO ₂ = 1 : 3.2-3.4; 35-40%) Species rat LD50 > 2000 mg/kg Source data of supplier		Reference substance	Slili Na ₂ Spe
Reference substance	Solice data of supplier Silicic acid, potassium salt (Molar ratio K_20 : SiO ₂ = 1 : 3.9-4.0; 28-30%)			LC: Dui Sou
	Species rat LD50 > 2000 mg/kg Source data of supplier		Reference substance	Sili K ₂ C Spe
Remarks	The poisonous effect of the product is caused by its alkalinity and not by substance-specifi c systemic			LC(Dui Sou
	characteristics.		Remarks	The

Safety Datasheet Version 3 1 / 18 01 2022

Irritant/corrosive effects

according to Regulation (EC) 1272/2008 (CLP) & 67/548/EEC

Irritant effect on skin	irritant
Irritant effect on eyes	irritant - risk of serious damage to eyes
Sensitization	non-sensitizing
Effects after repeated or (subacute, subchronic, cl	r prolonged exposition ronic)
Experience in practice	Irritating effects on the skin and mucous membrane. Risk of serious damage to eyes.
Other information	When handled appropiately, even after long years of experience with this product, no adverse health effects are known.

product, data are used as cross

Remarks	Ecotoxicological data are taken from a similar product of the same type.
Reference substance	Slilicic acid, sodium salt (Molar ratio Na ₂ O : SiO ₂ = 1 : 3.36; 35%) Species Brachidanio rerio LC5O > 2000 mg/l Duration of exposure 96 h Source data of supplier
Reference substance	Silicic acid, potassium salt (Molar ratio K ₂ O : SiO ₂ = 1 : 3.9-4.0; 29%) Species Leuciscus idus LCO > 500 mg/l Duration of exposure 48 h Source data of supplier
Remarks	The ecotoxic effect of the product is mainly due to its alkalinity.



Ecotoxicological data are taken from a

Daphnia toxicity

Remarks

(Comp. A)

according to Regulation (EC) 1272/2008 (CLP) & 67/548/EEC

13. Disposal considerations

Safety

Datasheet

Disposal recommendations for the product

EWC waste code: O6 O2 O5 other bases. Dilution and neutralization with acid. After solidification (e.g. as $CaSiO_3$ precipitate), landfi II in accordance with local authorities. Re-use without reprocessing as long as not solidified.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

14. Transport information

Land transport ADR/RID Not classifi ed as dangerous according to transport regulations

Sea transport IMGD/GGVSee)

Not classifi ed as dangerous according to transport regulations

Air transport

Not classifi ed as dangerous according to transport regulations

15. Regulatory information

15.1. Safety, health and environmental regulations/ legislations specific for the substance or mixture

The product is classified and labelled in accordance with EC Directive 99/45/EC.

Water Hazard Class (Ger.) WGK 1

Registration no. EC 215-687-4

15.2. Chemical Safety Assessment

Chemical Safety Assessment has been carried out for the substance. See Exposure scenario attached.

	similar product of the same type.
Reference substance	Slilicic acid, sodium salt (Molar ratio Na ₂ O : SiO ₂ = 1 : 3.2; 35%) Species Daphnia magna ECO > 2000 mg/l Duration of exposure 48 h Source data of supplier
Reference substance	Silicic acid, potassium salt (Molar ratio $K_20: SiO_2 = 1: 3.9-4.0; 29\%$) Species Daphnia magna ECO > 500 mg/l Duration of exposure 24 h Source data of supplier
Remarks	The ecotoxic effect of the product is mainly due to its alkalinity.
Bacteria toxicity	
Remarks	Ecotoxicological data are taken from a similar product of the same type.
Reference substance	Slilicic acid, sodium salt (Molar ratio Na ₂ O : SiO ₂ = 1 : 3.36; 35%) Species Pseudomonas putida ECO > 1000 mg/l Duration of exposure 48 h Source data of supplier
Remarks	The ecotoxic effect of the product is mainly due to its alkalinity.
Biodegradability	
Remarks	Inorganic product, cannot be eliminated from the water by biological purifi cation processes.

Behaviour in sewers (waste treatment plants)

The product is an alkaline solution. Neutralization is normally necessary before a waste water is discharged into sewage treatment plants. When low concentrations are discharged correctly into adapted biological sewage traetment plants, disturbance of the degradation activity of activated sludge is not likely.

SIE

(Comp. A)

16. Other information

Safety Datasheet Version 3 1 / 18 01 2022

EXPOSURE SCENARIO

according to Regulation (EC) 1272/2008 (CLP) & 67/548/EEC

Hazard symbols		Title	Workplace exposure to sodium silicate (EC 215-687-4)
Xi	Irritant.	Use Descriptor	Sector of Use: SU 3 and SU 22
Skin irrit. 2 Eye dam. 1	Skin irritation. Serious eye damage.		Process Categories (PROC): 1, 2, 3, 4, 5, 6, 7, 8a, 8b, 9, 10, 11, 13, 14, 22, 23, 24, 25
R-Phrases			Environmental Release Categories: not required
R38	Irritating to skin.	Processes, tasks,	Manufacture of the substance as well
R41	Risk of serious damage to eyes.	activities covered	as industrial and professional uses.
S- Phrases		Section 2	Operational conditions and risk management measures.
S26	In case of contact with eyes, rinse im- mediately with plenty of water and seek medical advice.		Whenever handling sodium silicate in a water preparation outside closed
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.		systems, depending on the use and concentration suitable personal protective equipment (gloves, goggles,
H- Phrases			dust masks or respiratiors) are the preferred and only measure of control.
H315	Causes skin irritation.		
H318	Causes serious eye damage.	Section 2.1	Control of worker exposure.
P- Phrases		Product characteristics Physical form of product	lliquid
P262	Do not get in eyes, on skin, or on clothing.	Concentration of substance in product	Covers percentage substance in the product up to 100 %, unless
P280	Wear protective gloves/protective clothing/eye protection/face protection.	Amounts used	otherwise stated. No limit
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	Frequency and duration of use Human factors not	Covers frequency up to: daily use, weekly, monthly, yearly.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove	infl uenced by risk management	Not applicable
	contact lenses, if present and easy to do. Continue rinsing.	Other Operational Conditions affecting	Assumes a good basic standard of occupational hygiene is implemented.



S1E Limited, Cooper House, Unit 2 Spring Hill Road, Park Springs, Grimethorpe, Barnsley S72 7BQ, UK.

worker exposure

The work occurs inside as well outside.

according to Regulation (EC) 1272/2008 (CLP) & 67/548/EEC

Exposure Estimation

Safety

Section 3

Section 4

3.1.

4.1.

Datasheet

Version 3.1 / 18.01.2022

Contributing Scenarios	Risk Management Measures.
PROC 1, 2, 3	Handle substance within a closed system. No other specific measures identified.
PROC 4, 5, 6, 8a, 8b, 9, 10, 13, 14, 22, 23, 24	Wear suitable gloves (tested to EN374). No other specifi c measures identified.
PROC 7, 11	Covers percentage substance in the pro- duct up to 25 %. Provide enhanced ge- neral ventilation by mechanical means. Wear suitable gloves (tested to EN374) and eye protection or Wear a respirator conforming to EN140 with Type A/P2 fi Iter. Avoid carrying out operation for more than 1 hour. Wear suitable gloves (tested to EN374) and eye protection.
Section 2.2	Control of environmental exposure.
	Not required, as soluble silicates, inclu- ding sodium/potassium silicate/disodium metasilicate, do not meet the criteria for classifi cation as dangerous to the environment according to 67/548/EEC (See Article 14.4 of REACH Regulation). Furthermore, as high production volume substances, soluble silicates have been

reviewed to a great extent for their exposure potential to the environment and the possible risks arising from their release (Van Dokkum et al. 2002, OECD SIDS 2004, HERA 2005, and CEES 2008). It was concluded that soluble silicates are currently of low priority for further work because of their low hazard

profile.

Health
The ECETOC TRA tool has been used to estimate worker exposures.
Guidance to check compliance with the Exposure Scenario
Health
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Con- ditions outlined in Section 2 are imple- mented. Where other Risk Management Measures/Operational Conditions are
adopted, then users should ensure that

levels.

risks are managed to at least equivalent

SIE